


# MODEL 630

## HINGED STEEL BELT CONVEYOR



735 Industrial Loop Road • New London, WI 54961-9612 • 920-982-6600 • Fax 920-982-7750 • Toll Free 800-558-3616

Website: [www.titanconveyors.com](http://www.titanconveyors.com) • Email: [sales@titanconveyors.com](mailto:sales@titanconveyors.com)

# MODEL 630

## HINGED STEEL BELT CONVEYOR



The **Model 630 Titan Hinged Steel Belt Conveyor** is the full profile unit in our complete line of hinged steel belt conveyors. The Model 630 is constructed of 10 gauge frame and 3/16" thick track. Four different configurations are available to provide complete flexibility to fit your requirements. A 2-1/2" pitch belt with 1-1/2" high stamped sidewings and 12 gauge apron is furnished as standard. The top mounted drive with 8-1/2" clearance is standard with optional side mounted drive available. Three different curve angles (30°, 45°, 60°) are offered as standard. (other degree curves optional). Marine bearings or outboard bearings can be supplied depending on the application. Consult the factory for further details.



MODEL 630 - 2-1/2" PITCH HINGED STEEL BELT MODELS		
	Standard	Options
<b>Belt Width</b>	4", 6", 8", 10", 12", 14", 16", 18", 24"	30", 36", 42"
<b>Belt Type</b>	2 1/2" pitch 1-1/2" standard stamped sidewing	Perforated, pimpled, pimpled & perforated, welded barrels, impact plates
<b>Curves</b>	30°, 45°, 60°	
<b>Frame</b>	8-5/8" deep formed 10 ga.	
<b>Drive</b>	1/2 H.P. 230/460/3/60	3/4, 1, 1-1/2, 2 H.; 115/230/1/60, 575/3/60 severed duty, inverter duty, brake motor
<b>Drive Sprocket</b>	6 Tooth, 5" P.D.	
<b>Chain Pull</b>	1500# without sidebars	3000# with sidebars
<b>OPTIONS</b>		
Drive location, H.P., fixed and variable speed, controls, coolant tanks, chutes, plumbing, top covers, chip suppressors, casters, liquid tight bottom pans, 3 bolt flange bearings or T-slot bearings at infeed, paint, supports, Belt: pimpled, perforated, welded barrels, impact plates, wiper cleats, cleat heights, sidebars on narrower belts		
Many other options available, consult factory representative		

**NOTE: Specifications subject to change without notice**